

CALMO UNI Entry

Efficient IPC with variety of interfaces



Up to 6x COM



8-36V DC



Optimized for
switch cabinets



Specifications

OS	<ul style="list-style-type: none"> • Windows 10/11 Pro / IoT • Linux 64-bit runnable
CPU	<ul style="list-style-type: none"> • Intel® Celeron J4005, 2x 2,7 GHz • Intel® Celeron J4105, 4x 2,5GHz • Intel® Pentium Silver J5005, 4x 2,8GHz
RAM	2x SO-DIMM DDR4 PC2400, max. 24 GB
Storage	1x M.2 B-Key 2242/2260/2280 SATA 1x 2,5" SSD/HDD
Graphics	Intel® UHD 600/605
Display Interface 1	DisplayPort 1.2 (4096 x 2160 @ 60Hz)
Display Interface 2	DisplayPort 1.2 (4096 x 2160 @ 60Hz)
Audio	Realtek ALC671 – 7.1 HD Audio
LAN	2x RJ45 @ 10/100/1000 Mbit/s (Intel® i210 + Realtek RTL8111G)
Power supply	DC-Input: 8-36V

Interfaces

Rear	<ul style="list-style-type: none"> • 2x USB 3.1 Gen1 2x USB 2.0 • 2x DisplayPort • 2x LAN • 2x RS-232 • 2x PS/2 • Audio • DC-in
Internal	<ul style="list-style-type: none"> • 1x PCIe x4 • 1x M.2 2230 • 1x miniPCIe • 8bit GPIO • USB 3.1 Stick

Additional data

Dimensions	250 x 52 x 191 mm
Weight	approx. 2 kg
IP-Protection	IP20
Temperature	0 °C to 55 °C
Special features	<ul style="list-style-type: none"> • Always-On • Wake-on-LAN • PXE-Boot • TPM 2.0 • Watchdog • System Guard • Recovery-BIOS
Optional extensions	<ul style="list-style-type: none"> • WiFi 6 incl. Bluetooth 5.0 • Additional 2x COM • USB Typ C • Risercard PCIe x4 for LowProfile • Internal 230V/65W Powersupply
Warranty	2 Years Bring-In (optional up to 5 Years)
Image stability	Available until 2024

For further information we invite you to visit:
www.calmo-pc.de

