## TOUGH. FANLESS. SPLASH PROTECTED.

## The Pokini TAB A10

Long-term availability

IP65 (dust and waterproof)

also available as a 8 " variant

drop resistance from 1 meter

supporting active disinfection

Optional with Protective frame for even more fall protection



- 10,1" (25,65 cm) capacitive 10 fi nger multi touch display with Corning-Gorilla-Glas (1.920 x 1.200 Px)
- Intel Atom BayTrail Z3795 quad core processor (up to 2.39 GHz, 2 MB L2 Cache)
- Intel HD Graphics with DirectX 11
- Windows 10 Pro
- up to 4 GB main memory LPDDR3 (soldered)
- up to 128 GB EMMC energy-saving flash memory
- Micro-SD card slot to 2 TB
- WLAN, Bluetooth, GPS/GLONASS, RFID
- LTE modem (optional)
- 8 MP camera with flash (rear)
- 2 MP camera (front)
- sensors: e-compass, accelerometer, ambient light sensor, proximity sensor
- USB 2.0, Audio (3,5 mm), Micro-USB (for charger), Kensington Lock
- 269 x 180,7 x 12,5 mm (W x H x D)
- approx. 758 g weight
- exchangeable Lithium Polymer battery with indicator LED
- very low power consumption 3.5 to 4 Watt battery run time: 8-10 hours
- drop resistant from 1.8 m (optional cover)
- 1 year bring-in (warrenty extension up to 3 years optional)
- fanless, cooling only passively on the housing surface









very low heat

- Video LED indicator above the display
- "Smart Back-Cover"-concept for various features:
  e.g. optional MSR, smart card reader, barcode, serial, LAN,...
  Further information at www.pokini.de/bce
- fixing points on back cover

## operating and storage conditions:

- operative: 10°C to +50°C
- storage: 20°C to +60°C
- operative humidity: 10% to 90%

## optional accessories

- docking station with 3x USB 3.0,
  LAN, Kensington Lock, charging pins
- rubberized Protective Case (Rubber Case)
- pen
- hand strap
- shoulder belt
- Back-Cover Extension
- mounting
- Case



